


The ALU collection **maximises playability**. Including lots of slides, bridges and dynamic elements, the ALU line encourages children to play, even those with disabilities. Its bright colours don't go unnoticed and the quality of materials guarantee high durability.

A x B			
A=9240mm	67m ²	1.50m	18
B=8650mm			



[Maintenance guide](#) | [Project sheet](#) | [CAD](#) | [Catalogue](#) | [Mounting instructions](#) | [HD image](#)

Materials:

Structure, Aluminium: 6005 cold extruded alloy and 2.5mm thick structural profiles. Extremely robust, offer excellent resistance to corrosion. All the aluminum profiles have special constructions in the grooves in which the connecting bolts are inserted for extra durability and greater anti-vandal resistance.

Panels, HDPE: high-density polyethylene characterised by its resistance to chemical abrasives. As a polymer, it is unaffected by corrosion. Due to its light elastic nature, it offers high resistance to impact, making it very difficult to break. As regards slides, they are made of a mixture of polyethylene and anti-static particles to reduce the accumulation of charge due to friction. However, it is possible that slide accumulate some static electricity in case of precise atmospheric conditions. Including a ground connection in every installation is recommended.

Nets, Anti-vandal reinforced rope: Ø 16mm, 6 twisted steel cables, covered in polypropylene. High durability plastic connectors.

Metallic parts: AISI-304 stainless steel, hot-dip galvanized steel and aluminium.

Fixings: electro galvanized and stainless steel quality 8.8 DIN267, AISI-304.

- None of the materials requires a specific treatment for its disposal.
- If the product is subject to severe use, maintenance should be increased.
- Don't use the product before the installation/maintenance is ready.
- Please check the maintenance instructions.


Biggest part (mm): 3340x40x40 / Heaviest part (kg): 44

IMPACT ZONE: security area and ground coverings according to the EN1176-1:2017 standard.

Spare parts availability: 10 years.

Ground anchoring screws not included.

Playful features:



Alternatives:



JALU10