



ILIS

Luminaire

ISABELINA



Classic decorative luminaire with an exclusive design including all necessary technical details for LED technology. Ideal for historical places and urban areas such as roads and squares. Ready for any intelligent lighting control solutions.

MAIN FEATURES:

- High efficacy. Up to 134 lm/W net
- From 20W to 80W
- 18 light distribution curves
- Zhaga Standard (Book 15)
- Tempered glass with sealing joint to obtain an IP66 rating
- Exclusive design
- Tool-less opening

APPLICATIONS:

- Residential areas
- Historical centres
- Green spaces
- Pedestrian areas and boulevards

[Project sheet](#) | [CAD](#) | [Catalogue](#) | [Mounting instructions](#) | [BIM](#) | [HD image](#)


BENITO

info@benito.com
tel. 93 852 1000

SPECIFICATIONS :

Housing material:	High pressure die-cast aluminium EN AC-43000, EN AC-43100, EN AC-43400, EN AC-44100, EN AC-47100 according to the UNE EN 1706 standard
Diffuser (optic system enclosure):	4mm tempered safety glass. UV filter
Fixing elements:	Stainless steel 18/8 - AISI 304
Housing:	Consists of three pieces: upper housing where the BENITO-NOVATILU LEDs module, the driver and the control electronics are located. Trapezoidal central block. Spider clamp
Sealing gaskets:	Silicone
IP rating (luminaire):	IP66
IP rating (optic system):	IP66
IK rating (impact resistance):	IK10
LEDs thermal dissipation:	Thermal dissipation through finless luminaire body, without conductive fluids. Passive convection dissipation ensuring thermal contact with the LED modules through a high-conductivity thermal transfer material
Anti-condensation valve:	Pressure-balancing valve to ensure moisture release, avoid condensation and maintain the luminaire IP tightness
Paint and finishes:	Polyester powder paint coating, electrostatically sprayed and sublimated in the oven. Resistant to corrosion
Colour:	Microtextured black. Optional: other colours and finishes
Mounting:	Top Ø60mm or by means of a 3/4" gas connector. Optional: Ø60mm not supplied
Tilt range:	
Maintenance:	Tool-less opening by means of threaded part. Modular concept for easy component replacement: LEDs, drivers, SPD
Recommended mounting height:	3 - 7 m
Driver:	Constant current adjustable and programmable driver. Embedded in the luminaire, pre-wired on a galvanised steel plate
Flow Reduction:	Dimmable driver 0-10V. Programmable on 5 levels. Optional: DALI 2. Includes the characteristics of Wireless, AOC, MTP, DTL
Ready4IOT - Connectivity:	- Autonomous multiple-level dimming or virtual midnight - Ready4IoT - Dimming by main voltage - Line switch
Surge protection device (SPD):	Type 2, 10kV and 20kA Transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life


DRAWING:



INSTALLATION:




V. 2023-10-24 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.




TECHNICAL DATA:

	REF.	Nº LEDs	Power W	I Driver mA	Real luminous flux (T) =85°C		Initial luminous flux (T) =25°C	
					Flux lm	Efficacy lm/W	Flux lm	Efficacy lm/W
Isabelina	ILIS	16	20	375	2600	130	2964	148
		16	30	563	3900	130	4446	148
		16	40	750	5160	129	5882	147
		16	60	1125	7680	128	8755	146
		32	80	750	10400	130	11856	148
		32	100	938	12900	129	14706	147

Luminous flux and efficiency at 4000°K and CRI>70.
 Luminous flux tolerance < +/-3%.
 Values may be subject to changes due to LED binning.



PHOTOMETRY:



*Show 4 recommended lighting distributions. Refer to the 18 typologies.

V. 2023-10-24 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.

LEDs MODULE:		
LEDs module:	BENITO-NOVATILU Zhaga standard for 16 and 32 LEDs. Check colour temperature, CRI and light distributions	
Replaceable module:	Yes	
LED:	5050	
Number of LEDs:	16 /32	
PCBs format:	2x Zhaga (Book 15) 2x4 or 2x Zhaga (Book 15) 2x8	
LED nominal efficacy:	172	
Colour temperature:	PC Amber, 2K2, 2K7, 3K, 4K, 5K	
Colour rendering index CRI:	>70 (optional >80)	
Average LED useful time L90B10:	L90B10 >100,000 hours	

OPTIC SPECIFICATIONS:		
Optic system:	PMMA lenses 2x2	
Light distributions:	18 light distribution curves	
Upward light output ratio ULOR:	0%	
Downward light output ratio DLOR:	100%	
Glare index:	Between D5 and D6 (depending on the light distribution)	
Luminous intensity category:	Between G*4 and G*6 (depending on the light distribution)	
Luminous flux CIE n°3:	>95%	
Photobiological safety:	RG0 (exempt of risk)	
Initial luminous flux Tj=25°C (up to):	lm	14706
Initial luminaire efficacy Tj=25°C (up to):	lm/W	148
Real luminous flux Tj=85°C (UNE EN 13032-4) (up to):	lm	12900
Real luminaire efficacy Tj=85°C (UNE EN 13032-4) (up to):	lm/W	130

ELECTRIC SPECIFICATIONS:		
Nominal maximum power (LEDs):	W	73
Maximum power consumed (luminaire):	W	80
Power range:	W	20 - 80W
Maximum current of LED:	mA	<500 (<50% I _{max})
Power supply protection classes IEC:	Class I and II	
Surge protection device (SPD):	Type 2, 10kV and 20kA Transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life	
Common and differential mode protection (SPD) Udc:	kV	10 and optional NTC
Max current (8/20) (SPD):	kA	20
Thermal phase disconnection (SPD):	Yes	
Input voltage:	Vac	220-240
Input voltage (max rate):	Vac	198-264
Input frequency:	Hz	47-63
Starting current:	A	<65
Duration of the starting voltage peak:	ms	<0.3
Driver efficacy:	>90%	
Power factor 100% consumption:	>0.98	
Power factor 50% consumption:	>0.95	
Total harmonic distortion (THD):	<10	
Power consumption on standby mode:	W	<0.4
Energy class:	A++ IPEA>1.15	

OPERATING CONDITIONS:		
Average LED useful time L90B10:	>100,000	
Average driver useful life to T _p <70°C:	100,000	
Average luminaire useful life L90B10 (TM-21):		
Ambient temperature (Ta):	°C	From -35°C to +50°C
Aerodynamic resistance (CxS):	m2	0.15
Vibration test (15Hz 3 axis):		
Guarantee:	years	5 years (extensible up to 10 years)

PACKAGING DIMENSIONS:		
Net weight	kg	12
Gross weight	kg	15
Luminaire dimensions (LxWxH)	mm	485x870
Packaging dimensions (LxWxH)	mm	500x500x910
Pieces per box	1	
Quantity per container 20ft		
Quantity per container 40ft		

CERTIFICATES:	
Security certificates:	EN 40 / EN 62031 / EN 62493 / EN 62471 / IEC 62778 / EN 61247-2-16
EMC certificates:	EN 55015 / EN 61547 / EN 61000-3-2 / EN 61000-3-3 / EN 61347-2-13 / EN 61347-1 / EN 62384
Other certifications:	IEC 62262 / EN 13032-4 / EN 62717 / EN 6272-1 / EN 6272-2-1 / EN 61643-14

Company Certifications



BENITO

info@benito.com
tel. 93 852 1000