




The CICLO LIGHT POINT, a decorative light fixture designed to address any lighting requirements that may arise in an urban development project, with all the features of the latest LED technology and a simple, minimalist, and non-invasive aesthetic language. With this light point and its multiple configurations, all the needs of each project can be addressed.

The CICLO LIGHT POINT consists of a cylindrical column and a combination of CICLO Floodlights that can be fully customized. Available in heights ranging from 4 to 8 meters, with the option to mount up to six or seven projectors. With the CICLO Floodlight, adjustable in both vertical and horizontal axes, and its LED technology features, the lighting designer can fine-tune the space's illumination, controlling every lumen.



Ref	H	Ø	A	B
CICLO 4m	4000	120	M18x500	200
CICLO 5m	5000	120	M18x500	200
CICLO 6m	6000	120	M18x500	200
CICLO 7m	7000	120	M22x500	300
CICLO 8m	8000	120	M22x500	300








APCM

# Floodlight CICLO M



Compact circular floodlight. Comprehensive range available in three sizes with extensive optical and light distributions from 15W up to 75W to cover all applications. Can be tilted in all directions thanks to its fixing bracket. Ready for any intelligent lighting control solutions.

## MAIN FEATURES:

- High efficiency. Up to 140 lm/W net
- 3 different sizes. From 15W to 75W
- 18 light distribution curves
- Zhaga Standard (Book 15)
- Tilting by means of a joint
- Several accessories for its fixing to a pole
- Optional RGBW with control DMX-513

## APPLICATIONS:

- Bicycle Lanes and Narrow Roads
- Pedestrian Zones
- Commercial and Tourist Streets
- Green Areas; Parks and Gardens
- Architectural; Buildings and Monuments
- Accent lighting; Trees and Sculptures

[Project sheet](#) | [CAD](#) | [Catalogue](#) | [HD image](#)


# BENITO

info@benito.com  
tel. 93 852 1000

SPECIFICATIONS :

Housing material:	High pressure die-cast aluminium EN AC-43000, EN AC-43100, EN AC-43400, EN AC-44100, EN AC-47100 according to the UNE EN 1706 standard
Diffuser (optic system enclosure):	5mm tempered safety glass. UV filter
Fixing elements:	Stainless steel 18/8 - AISI 304
Housing:	Double compartment: driver / LED module
Sealing gaskets:	Silicone foam
IP rating (luminaire):	IP66
IP rating (optic system):	IP66
IK rating (impact resistance):	IK08
LEDs thermal dissipation:	Thermal dissipation through finless luminaire body, without conductive fluids. Passive convection dissipation ensuring thermal contact with the LED modules through a high-conductivity thermal transfer material
Anti-condensation valve:	Pressure-balancing valve to ensure moisture release, avoid condensation and maintain the luminaire IP tightness
Paint and finishes:	Polyester powder paint coating, electrostatically sprayed and sublimated in the oven. Resistant to corrosion
Colour:	Black. Optional; other colours
Mounting:	Joint adaptable to clamp for simple or double pole, and TOP 60 mm
Tilt range:	From -60° to 60°
Maintenance:	Top opening. Modular concept for easy component replacement: LEDs, drivers, SPD
Recommended mounting height:	4-8 m
Driver:	Constant current adjustable and programmable driver. Embedded in the luminaire, pre-wired on a galvanised steel plate
Flow Reduction:	Dimmable driver 0-10V. Programmable on 5 levels. Optional: DALI 2. Includes the characteristics of Wireless, AOC, MTP, DTL
Ready4IoT - Connectivity:	- Autonomous multiple-level dimming or virtual midnight - Ready4IoT - Dimming by main voltage - Line switch
Surge protection device (SPD):	Type 2, 10kV and 20kA transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life


DRAWING:



INSTALLATION:




V. 2024-02-23 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.




TECHNICAL DATA:

CICLO M	REF.	Nº LEDs	Power W	I Driver mA	Real luminous flux (T) =85°C		Initial luminous flux (T) =25°C	
					Flux lm	Efficacy lm/W	Flux lm	Efficacy lm/W
					2600	130	2964	148
	APCM140	16	20	375	5000	125	5700	143

Luminous flux and efficiency at 4000°K and CRI>70.  
Luminous flux tolerance < +/-3%.  
Values may be subject to changes due to LED binning.



PHOTOMETRY:



\*Show 4 recommended lighting distributions. Refer to the 18 typologies.

V. 2024-02-23 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.

### LEDs MODULE:

LEDs module:	BENITO-NOVATILU Zhaga standard for 8, 12 and 16 LEDs. Check colour temperature, CRI and light distributions	
Replaceable module:	Yes	
LED:	5050	
Number of LEDs:	16	
PCBs format:	2 Zhaga (Book 15) 2x8	
LED nominal efficacy:	172	
Colour temperature:	PC Amber, 2K2, 2K7, 3K, 4K, 5K	
Colour rendering index CRI:	>70 (optional >80)	
Average LED useful time L90B10:	L90B10 >100.000 hours	

### OPTIC SPECIFICATIONS:

Optic system:	PMMA lenses 2x2	
Light distributions:	18 light distribution curves	
Upward light output ratio ULOR:	0%	
Downward light output ratio DLOR:	100%	
Glare index:	Between D5 and D6 (depending on the light distribution)	
Luminous intensity category:	Between G*4 and G*6 (depending on the light distribution)	
Luminous flux CIE n°3:	>95%	
Photobiological safety:	RG0 (exempt of risk)	
Initial luminous flux Tj=25°C (up to):	lm	5700
Initial luminaire efficacy Tj=25°C (up to):	lm/W	130
Real luminous flux Tj=85°C (UNE EN 13032-4) (up to):	lm	5000
Real luminaire efficacy Tj=85°C (UNE EN 13032-4) (up to):	lm/W	125

### ELECTRIC SPECIFICATIONS:

Nominal maximum power (LEDs):	W	36
Maximum power consumed (luminaire):	W	40
Power range:	W	20W - 40W
Maximum current of LED:	mA	<400 (<50% I <sub>max</sub> )
Power supply protection classes IEC:	Class I and II	
Surge protection device (SPD):	Type 2, 10kV and 20kA transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life	
Common and differential mode protection (SPD) Udc:	kV	10 and optional NTC
Max current (8/20) (SPD):	kA	20
Thermal phase disconnection (SPD):	Yes	
Input voltage:	Vac	220-240
Input voltage (max rate):	Vac	198-264
Input frequency:	Hz	47-63
Starting current:	A	<65
Duration of the starting voltage peak:	ms	<0,3
Driver efficacy:	>90%	
Power factor 100% consumption:	>0,98	
Power factor 50% consumption:	>0,95	
Total harmonic distortion (THD):	<10	
Power consumption on standby mode:	W	<0,4
Energy class:	A++ IPEA>1,15	

### OPERATING CONDITIONS:

Average LED useful time L90B10:	hours	100.000
Average driver useful life to Tp <70°C:	hours	100.000
Average luminaire useful life L90B10 (TM-21):	hours	96.000
Ambient temperature (Ta):	°C	from -35°C to +50°C
Aerodynamic resistance (CxS):	m2	0,07
Vibration test (15Hz 3 axis):		
Guarantee:	years	5 years (extensible up to 10 years)

### PACKAGING DIMENSIONS:

Net weight	kg	3,8
Gross weight	kg	
Luminaire dimensions (LxWxH)	mm	Ø 220 mm x 258 mm
Packaging dimensions (LxWxH)	mm	
Pieces per box		1
Quantity per container 20ft		
Quantity per container 40ft		

### CERTIFICATES:

Security certificates:	EN 60598-1 / EN 60598-2-5 / EN 62493 / IEC 62471
EMC certificates:	EN 55015 / EN 61547 / EN 61000-3-2 / EN 61000-3-3 / EN 61347-2-13 / EN 61347-1 / EN 62384
Other certifications:	IEC 62262 / EN 13032-4 / EN 62717 / EN 6272-1 / EN 6272-2-1 / EN 61643-11

Company Certifications



V. 2024-02-23 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.

**BENITO**

info@benito.com  
tel. 93 852 1000