


ILDH2

Floodlight DECO



Belongs to the Essentials range, a set of luminaires of different types and styles that share a common aesthetic. Elegant and contemporary design ideal for all kind of applications, especially road and residential ones. Can be installed on 4m to 8 m poles. Optical design optimised for a perfect glare control and cut-off suitable for pedestrians without emission to the upper hemisphere.

MAIN FEATURES:

- High efficacy. Up to 142 lm/W net
- Essentials range. From 20W to 120W
- Finless passive dissipation
- Tool-less opening
- 18 light distribution curves
- Zhaga Standard (Book 15)
- Ready 4IoT. Ready for any intelligent lighting control solution

APPLICATIONS:

- Urban and residential areas
- Parks and green spaces
- Maritime promenades
- Pedestrian areas
- Cycle lanes and ≤ 30 km/h areas

[CAD](#) | [Catalogue](#) | [HD image](#)


BENITO

info@benito.com
tel. 93 852 1000

SPECIFICATIONS :

Housing material:	High pressure die-cast aluminium EN AC-43000, EN AC-43100, EN AC-43400, EN AC-44100, EN AC-47100 according to the UNE EN 1706 standard
Diffuser (optic system enclosure):	5mm tempered safety glass. UV filter
Fixing elements:	Stainless steel 18/8 - AISI 304
Housing:	Double compartment: driver / LED module
Sealing gaskets:	Silicone foam
IP rating (luminaire):	IP66
IP rating (optic system):	IP66
IK rating (impact resistance):	IK09
LEDs thermal dissipation:	Thermal dissipation through finless luminaire body, without conductive fluids. Passive convection dissipation ensuring thermal contact with the LED modules through a high-conductivity thermal transfer material
Anti-condensation valve:	
Paint and finishes:	Polyester powder paint coating, electrostatically sprayed and sublimated in the oven. Resistant to corrosion
Colour:	Matte black RAL 9005. Optional: other colours
Mounting:	Lateral with fixing bracket
Tilt range:	From -120° to +120°
Maintenance:	Easy, tool-less opening. Modular concept for easy component replacement: LEDs, drivers, SPD
Recommended mounting height:	4 - 8 m
Driver:	Constant current adjustable and programmable driver. Embedded in the luminaire, pre-wired on a galvanised steel plate
Flow Reduction:	Dimmable driver 0-10V. Programmable on 5 levels. Optional: DALI 2. Includes the characteristics of Wireless, AOC, MTP, DTL
Ready4IOT - Connectivity:	- Autonomous multiple-level dimming or virtual midnight - Ready4IoT - Dimming by main voltage - Line switch
Surge protection device (SPD):	Type 2, 10kV and 20kA transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life


DRAWING:



INSTALLATION:




V. 2024-02-23 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.




TECHNICAL DATA:

	REF.	N° LEDs	Power W	I Driver mA	Real luminous flux (T) =85°C		Initial luminous flux (T) =25°C	
					Flux lm	Efficacy lm/W	Flux lm	Efficacy lm/W
DECO HORIZON	ILDH	16	20	375	2842	142	3240	162
		16	30	563	4242	141	4836	161
		16	40	750	5642	141	6432	161
		32	40	375	5680	142	6475	162
		32	60	563	8460	141	9644	161
		32	80	750	11280	141	12859	161
		48	80	500	11360	142	12950	162
		48	100	625	14100	141	16074	161
		48	120	750	16920	141	19289	161

Luminous flux and efficiency at 4000°K and CRI>70.
Luminous flux tolerance < +/-3%.
Values may be subject to changes due to LED binning.



PHOTOMETRY:



*Show 4 recommended lighting distributions. Refer to the 18 typologies.

V. 2024-02-23 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.

LEDs MODULE:

LEDs module:	BENITO-NOVATILU Zhaga standard for 8 and 16 LEDs. Check colour temperature, CRI and light distributions		
Replaceable module:	Yes		
LED:	5050		
Number of LEDs:	16-32-48		
PCBs format:	1 o 2 Zhaga (Book 15) 2x8 o 2 Zhaga (Book 15) 2x8 + 2 Zhaga (Book 15) 2x4		
LED nominal efficacy:	172 lm/W		
Colour temperature:	PC Amber, 2K2, 2K7, 3K, 4K, 5K, 5K		
Colour rendering index CRI:	>70 (optional >80)		
Average LED useful time L90B10:	L90B10 >100.000 horas		

OPTIC SPECIFICATIONS:

Optic system:	PMMA lenses 2x2		
Light distributions:	18 light distribution curves		
Upward light output ratio ULOR:	0%		
Downward light output ratio DLOR:	100%		
Glare index:	Between D5 and D6 (depending on the light distribution)		
Luminous intensity category:	Between G*4 and G*6 (depending on the light distribution)		
Luminous flux CIE n°3:	>95%		
Photobiological safety:	RG0 (exempt of risk)		
Initial luminous flux Tj=25°C (up to):	lm	19289	
Initial luminaire efficacy Tj=25°C (up to):	lm/W	162	
Real luminous flux Tj=85°C (UNE EN 13032-4) (up to):	lm	16920	
Real luminaire efficacy Tj=85°C (UNE EN 13032-4) (up to):	lm/W	142 (Rendimiento = 82.6 % lm/W (Real 85°C) ÷ lm/W (Nominal Led))	

ELECTRIC SPECIFICATIONS:

Nominal maximum power (LEDs):	W	108	
Maximum power consumed (luminaire):	W	120	
Power range:	W	20 - 120W	
Maximum current of LED:	mA	<400 (<50% I _{max})	
Power supply protection classes IEC:	Class I and II		
Surge protection device (SPD):	Type 2, 10kV and 20kA transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life		
Common and differential mode protection (SPD) Udc:	kV	10 y NTC opcional	
Max current (8/20) (SPD):	kA	20	
Thermal phase disconnection (SPD):	Yes		
Input voltage:	Vac	220-240	
Input voltage (max rate):	Vac	198-264	
Input frequency:	Hz	47-63	
Starting current:	A	<65	
Duration of the starting voltage peak:	ms	<0,3	
Driver efficacy:	>90%		
Power factor 100% consumption:	>0,98		
Power factor 50% consumption:	>0,95		
Total harmonic distortion (THD):	<10		
Power consumption on standby mode:	<0,4		
Energy class:	A++ IPEA>1,15		

OPERATING CONDITIONS:

Average LED useful time L90B10:	>100.000	
Average driver useful life to Tp <70°C:	100.000	
Average luminaire useful life L90B10 (TM-21):	72.167	
Ambient temperature (Ta):	°C	de -35°C a +50°C
Aerodynamic resistance (CxS):	m2	0,070
Vibration test (15Hz 3 axis):		
Guarantee:	years	5 years (extensible up to 10 years)

PACKAGING DIMENSIONS:

Net weight	kg	7,5
Gross weight	kg	9
Luminaire dimensions (LxWxH)	mm	450x450x135
Packaging dimensions (LxWxH)	mm	520x520x170
Pieces per box	1	
Quantity per container 20ft		
Quantity per container 40ft		

CERTIFICATES:

Security certificates:	EN 60598-1 / EN 60598-2-3 / IEC 62471		
EMC certificates:	EN 55015 / EN 61547 / EN 61000-3-2 / EN 61000-3-3 / EN 61347-2-13 / EN 61347-1 / EN 62384		
Other certifications:	IEC 62262 / EN 13032-4 / EN62031 / EN 16474 / ISO 9227 / EN 60068-2-11 / ISO 10289 / EN 61643-11		

Company Certifications



BENITO

info@benito.com
tel. 93 852 1000