


APMXXLR

Floodlight

MILAN XXL RGBW



RGBW flat floodlight with low wind resistance. Comprehensive range available in four sizes with extensive optical and light distributions from 120W up to 480W to cover all applications. Can be tilted in all directions thanks to its fixing bracket. Ready for any intelligent lighting control solutions thanks to the DMX-512 protocol.

MAIN FEATURES:

- High efficiency. Up to 140 lm/W real
- 3 different sizes. From 120W to 480W
- 4 Groups of RGBW LEDs
- Independent dimming control for each color via DMX-512 protocol
- Double cavity, Driver and Optical Group
- High robustness to 5G vibrations

APPLICATIONS:

- Commercial and Tourist Streets
- Architectural; Buildings and Monuments

DETAILS:



[Project sheet](#) | [CAD](#) | [Mounting instructions](#) | [HD image](#)


BENITO

info@benito.com
tel. 93 852 1000

SPECIFICATIONS :

Housing material:	Die-cast aluminium casting EN AC-47000 of type EN AC-43000, EN AC-43100, EN AC-43400, EN AC-44100, EN AC-47100 according to standard UNE EN 1706.
Diffuser (optic system enclosure):	5mm tempered glass. Filters UV rays.
Fixing elements:	18/8 Stainless Steel - AISI 304
Housing:	Double Cavity: Driver / LED Module
Sealing gaskets:	Silicone Foam
IP rating (luminaire):	IP66
IP rating (optic system):	IP66
IK rating (impact resistance):	IK09 - IK10
LEDs thermal dissipation:	Heat dissipation through the luminaire body, without external fins or conductive fluids. Passive heat dissipation through convection, ensuring thermal contact between the LED modules through highly conductive heat transfer material.
Anti-condensation valve:	Pressure compensation valve that ensures moisture evacuation, preventing condensation and maintaining the luminaire's IP rating.
Paint and finishes:	Polyester powder coating, electrostatically sprayed and oven-sublimated. Corrosion-resistant.
Colour:	RAL 9022 color and other colors on request
Mounting:	Steel lyre
Tilt range:	Adjustable Floodlight from -120° to 120° inclination.
Maintenance:	Top-opening for easy handling. Replaceable modules: LEDs, drivers, SPDs.
Recommended mounting height:	10 - 14 m
Driver:	Dimmable and programmable constant current driver. Built into the luminaire, pre-wired on a steel plate. .
Flow Reduction:	Dimmable Driver via DMX-512 protocol through a decoder.
Ready4IoT - Connectivity:	- Autonomous multiple-level dimming or virtual midnight - Ready4IoT - Dimming by main voltage - Line switch
Surge protection device (SPD):	Type 2, 10-20kV and 20kA transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life
DarkSky Approved	

DRAWING:



INSTALLATION:




V. 2026-03-06 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.

TECHNICAL DATA:




	REF.	Nº LEDs	Power W	I Driver mA	Real luminous flux (T) =85°C		Initial luminous flux (T) =25°C	
					Flux lm	Efficacy lm/W	Flux lm	Efficacy lm/W
P MILAN XXL RGBW	ALMXXLR480	168	300	536	31500	105	35910	120
		168	350	625	36750	105	41895	120
		168	400	714	41600	104	47424	119
		168	460	857	48960	102	55814	116



Luminous fluxes and efficiencies with all four RGBW channels at 100%

PHOTOMETRY



*Show 4 recommended lighting distributions. Refer to the 18 typologies.

V. 2026-03-06 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.

LEDs MODULE:		
LEDs module:	BENITO PCB with 168 Compact RGBW LEDs	
Replaceable module:	Yeah	
LED:	3535	
Number of LEDs:	48	
PCBs format:		
LED nominal efficacy:		
Colour temperature:	R - G - B - W	
Colour rendering index CRI:		
Average LED useful time L90B10:	L90B10 >100,000 hours	

OPTIC SPECIFICATIONS:		
Optic system:	Circular PMMA Lenses	
Light distributions:	18 light distribution curves	
Upward light output ratio ULOR:	0%	
Downward light output ratio DLOR:	100%	
Glare index:	Between D5 and D6 (depending on the light distribution)	
Luminous intensity category:	Between G*4 and G*6 (depending on the light distribution)	
Luminous flux CIE n°3:	>95%	
Photobiological safety:	RG0 (risk-free)	
Initial luminous flux Tj=25°C (up to):	lm	55814
Initial luminaire efficacy Tj=25°C (up to):	lm/W	105
Real luminous flux Tj=85°C (UNE EN 13032-4) (up to):	lm	48960
Real luminaire efficacy Tj=85°C (UNE EN 13032-4) (up to):	lm/W	105

ELECTRIC SPECIFICATIONS:		
Nominal maximum power (LEDs):	W	432
Maximum power consumed (luminaire):	W	480
Power range:	W	0 - 480W
Maximum current of LED:	mA	<500 (<50% I _{max})
Power supply protection classes IEC:	Class I and II	
Surge protection device (SPD):	Type 2, 10-20kV and 20kA transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life	
Common and differential mode protection (SPD) Udc:	kV	10 and optional NTC
Max current (8/20) (SPD):	kA	20
Thermal phase disconnection (SPD):	Yes	
Input voltage:	Vac	220-240
Input voltage (max rate):	Vac	198-264
Input frequency:	Hz	47-63
Starting current:	A	<65
Duration of the starting voltage peak:	ms	<0.3
Driver efficacy:	>90%	
Power factor 100% consumption:	>0.98	
Power factor 50% consumption:	>0.95	
Total harmonic distortion (THD):	<10	
Power consumption on standby mode:	W	<0.4
Energy class:	C (According to EU Regulation 2019/2015 EPREL) - A++ IPEA>1.15.	

OPERATING CONDITIONS:		
Average LED useful time L90B10:	hours	>100,000
Average driver useful life to T _p <70°C:	hours	100,000
Average luminaire useful life L90B10 (TM-21):	hours	72,167
Ambient temperature (Ta):	°C	From -35°C to +50°C
Aerodynamic resistance (CxS):	m2	0.078
Vibration test (15Hz 3 axis):		
Guarantee:	years	5 years (extensible up to 10 years)

PACKAGING DIMENSIONS:		
Net weight	kg	20
Gross weight	kg	21.8
Luminaire dimensions (LxWxH)	mm	727x558x107
Packaging dimensions (LxWxH)	mm	785x610x165
Pieces per box	1	
Quantity per container 20ft	325	
Quantity per container 40ft	689	

CERTIFICATES:	
Security certificates:	EN 60598-1 / EN 60598-2-5 / EN 62493 / IEC 62471
EMC certificates:	EN 55015 / EN 61547 / EN 61000-3-2 / EN 61000-3-3 / EN 61347-2-13 / EN 61347-1 / EN 62384
Other certifications:	IEC 62262 / EN 13032-4 / EN 62717 / EN 6272-1 / EN 6272-2-1 / EN 61643-11

Company Certifications



BENITO

info@benito.com
tel. 93 852 1000