




H2208
Bollard

PLAZA 220 semi-automatic telescopic



Metal
Key

Regulations and certifications:



With key, Ø220, height 500 or 29.53"

Bollard designed for access control on public roads, in communities, companies, etc. Automatic, easy and fast raising, manual lowering.


Once lowered, it remains flush with the ground, avoiding tripping.

Automatic locking in both raised and lowered position, unlocking by DIN3223 triangular key.

		H2204	H2208	H2208H75
DIMENSIONS AND MATERIALS	HEIGHT FROM GROUND LEVEL	19.69"	29.72"	29.53"
	THICKNESS	0.16"	0.31"	0.31"
	BOLLARD DIAMETER	8.66"	8.66"	8.66"
	BOX DIMENSIONS	13.39x13.39x26.38"	13.39x13.39x26.38"	13.39x13.39x38.98"
	BOLLARD MATERIAL	Stainless Steel Satin AISI 304	Stainless Steel Satin AISI 304	Stainless Steel Satin AISI 304
FEATURES	MOTOR POWER	400 Newton	500 Newton	700 Newton
FUNCTIONAL FEATURES	SYSTEM	Gas Cylinder	Gas Cylinder	Gas Cylinder
	WORKING FREQUENCY	More than 500,000	More than 500,000	More than 500,000
	IMPACT RESISTANCE	40,000 joules	80,000 joules	80,000 joules
	REFLECTIVE BAND	Yes	Yes	Yes
	LIGHTED CROWN		Optional	Optional

BENITO

info@benito.com
tel. 93 852 1000



Ref.	Ø A	B	C	D	E		Wt
H220 8	Ø8.66 "	26.38' "	19.69' "	10.79' "	13.39' "	0.31"	-
H220 4	Ø8.66 "	26.38' "	19.69' "	10.79' "	13.39' "	0.16"	351 Lbs

Semi-Automatic Telescopic with key and LED Ø220 x 500



Bollard available:

LED crown for better night visibility.
Reflective band that enhances safety.



Downloads: [Project sheet](#) | [CAD](#) | [Mounting instructions](#) | [BIM](#)



V. 2026-06-11 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.