

MAD51

Marquee

DIEDRIK



Regulations and certifications:




A 2x2 meter climate-controlled shelter, ideal for all types of leisure areas. Its robust structure is made of wood with steel joints treated with the FERRUS protective process and finished in wrought iron black, ensuring high resistance and durability against inclement weather. The perfect solution for projects requiring both functionality and design.

Materials & Finishes:

Steel with a hot-dip galvanizing treatment to protect it from corrosion. Our galvanizing process complies with the UNE EN ISO 1461:2009 standard and involves immersion in a crucible of molten zinc at 450°C, during which a reaction occurs between zinc and steel resulting in different layers of alloy between the two metals, culminating in an external coating of pure zinc. To ensure proper application of the process, it is essential to subject the pieces to a preliminary process of degreasing, pickling, and fluxing.

Hardwood treated with LIGNUS: Wood from responsible forestry. Density greater than 930kg/m³, at 12% humidity, treated with a triple-layer LIGNUS coating, fungicide, insecticide, and water-repellent that provides protection against moisture penetration. Final finish with a layer of natural pigment in a satin finish, which provides additional protection against UV rays, the main cause of deterioration in this type of material.



Ref.	A	B	H
MAD50	85.24"	85.24"	94.49"
MAD51	85.24"	85.24"	94.49"
MAD52	252.76"	85.24"	94.49"

DIEDRIK PLUS
MAD52



BENITO

info@benito.com
tel. 93 852 1000

Downloads:



V. 2026-06-17 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.