




UM320

Bench


Roda



Black forje
casting



Hard
wood



M10 bolts
fixing

Regulations and certifications:




RODA Bench , 78.54" long, overall dimensions (length x height x depth) 78.54x29.53x24.41", manufactured with ductile iron legs (treated with the Ferrus triple-layer protective coating for iron, guaranteeing optimal corrosion resistance). Finished with epoxy primer and black wrought iron polyester powder coating. Ten hardwood planks (treated with Lignus triple-layer coating, a fungicidal, insecticidal, and water-repellent protective coating) in a natural finish. Stainless steel screws. Prepared for anchoring with M10 expansion bolts depending on the surface and project.

Optional not included: Customizable marking with 2.91x1.38" aluminum plate or milled board.

Materials & Finishes:

Ductile Iron treated with FERRUS: iron protection process that ensures optimal corrosion resistance. The Ferrus treatment consists of three layers applied after cleaning all dirt and impurities using shot blasting, involving an electrolytic bath followed by an epoxy primer and a final coating of polyester powder paint. Forged black colour

Hardwood treated with LIGNUS: Wood from responsible forestry. Density greater than 930kg/m³, at 12% humidity, treated with a triple-layer LIGNUS coating, fungicide, insecticide, and water-repellent that provides protection against moisture penetration. Final finish with a layer of natural pigment in a satin finish, which provides additional protection against UV rays, the main cause of deterioration in this type of material.



Ref.	A	B	H	H1	Wt
UM320	78.54"	24.41"	29.53"	16.34"	133 Lbs
UM320S	23.43"	24.41"	29.53"	16.34"	76 Lbs

Roda
UM320S



BENITO

info@benito.com
tel. 93 852 1000

Downloads: [Project sheet](#) | [CAD](#) | [Mounting instructions](#) | [BIM](#)

