



UM327V

Bench

MINSK-V

By BRC Design © ® BENITO




Controlled logging



Olive Casting



Inclusive Product



Hard wood

Regulations and certifications:




MINSK-V design Bench , total dimensions (length x height x depth) 70.87x32.28x23.23", manufactured with ductile iron legs (treated with the Ferrus process, the triple-layer protector for iron, which guarantees optimal corrosion resistance), with olive-colored polyester powder paint coating and five natural tropical wood planks (treated with a triple-layer Lignus coating, a fungicidal, insecticidal and water-repellent protector). Stainless steel screws. Prepared for anchoring with M10 expansion bolts according to surface and project.

Optional not included: Customizable marking with 2.91x1.38" aluminum plate or milled board.

Materials & Finishes:

Ductile Iron treated with FERRUS: iron protection process that ensures optimal corrosion resistance. The Ferrus treatment consists of three layers applied after cleaning all dirt and impurities using shot blasting, involving an electrolytic bath followed by an epoxy primer and a final coating of polyester powder paint. Forged black colour

Hardwood treated with LIGNUS: Wood from responsible forestry. Density greater than 930kg/m³, at 12% humidity, treated with a triple-layer LIGNUS coating, fungicide, insecticide, and water-repellent that provides protection against moisture penetration. Final finish with a layer of natural pigment in a satin finish, which provides additional protection against UV rays, the main cause of deterioration in this type of material.



Ref.	A	B	C	H	H1	Wt
UM327	70.87"	23.23"	17.72"	32.28"	18.11"	185 Lbs
UM327S	27.56"	23.23"	17.72"	32.28"	18.11"	185 Lbs

BENITO

info@benito.com
tel. 93 852 1000

Minsk
UM327



MINSK-O
UM327O



MINSK-R
UM327R



Downloads: [Project sheet](#) | [CAD](#) | [Mounting instructions](#) | [BIM](#)

