UM377X

Bench

Quatro

By Carles Casamor - Marta Gabàs © ® BENITO

Regulations and certifications:

ISO 9001 · ISO 50001 · ISO 14001 · ISO 45001

QUATRO designer Bench , total dimensions (length x height x depth) 78.74x31.30x26.18", made with galvanized steel legs (treated with the Ferrus process, the triple-layer protector for iron, which guarantees optimal corrosion resistance), with epoxy primer and a red oxide oxiron finish. Five natural tropical wood planks (treated with a triple-layer Lignus coating, a fungicidal, insecticidal and water-repellent protector). Stainless steel screws. Prepared for anchoring with M10 expansion bolts according to surface and project.
Optional items not included: Customizable marking with 2.91x1.38" aluminum plate or milled board.

Ref.	A	B	H	H1	Wt
UM377X	78.74"	26.18"	31.30"	17.72"	248 Lbs
UM377SM	24.41"	26.18"	31.30"	17.72"	110 Lbs

Quatro S
UM377SM

BENITO

info@benito.com
tel. 93 852 1000

Bench **Quatro** UM377X

Materials & Finishes:

Ductile Iron treated with FERRUS: iron protection process that ensures optimal corrosion resistance. The Ferrus treatment consists of three layers applied after cleaning all dirt and impurities using shot blasting, involving an electrolytic bath followed by an epoxy primer and a final coating of polyester powder paint.Forged black colour

Hardwood treated with LIGNUS: Wood from responsible forestry. Density greater than 930kg/m³, at 12% humidity, treated with a triple-layer LIGNUS coating, fungicide, insecticide, and water-repellent that provides protection against moisture penetration. Final finish with a layer of natural pigment in a satin finish, which provides additional protection against UV rays, the main cause of deterioration in this type of material.

Steel with a hot-dip galvanizing treatment to protect it from corrosion. Our galvanizing process complies with the UNE EN ISO 1461:2009 standard and involves immersion in a crucible of molten zinc at 450°C, during which a reaction occurs between zinc and steel resulting in different layers of alloy between the two metals, culminating in an external coating of pure zinc. To ensure proper application of the process, it is essential to subject the pieces to a preliminary process of degreasing, pickling, and fluxing.

Downloads: *Project sheet* | *CAD* | *Mounting instructions* | *BIM*

BENITO

info@benito.com
tel. 93 852 1000

The Ferrus treatment consists of three layers applied after shot cleaning all impurities: an electrolytic bath, an epoxy coating and a rust red oxiron polyester paint coating.
Four 140 x 70 mm tropical wood boards treated with Lignus, a fungicide, insecticide and waterproof agent. Natural colour finish.
Stainless steel screws.

Recommended anchoring: by means of M10 expansion bolts depending on the surface and the project.

info@benito.com
tel. 93 852 1000