UM397SE

Chair

Leman

By Compagnies Desrues © ® BENITO

Grey Casting

Hard wood

Regulations and certifications:

ISO 9001 ISO 50001 ISO 14001 ISO 45001

Chair made with ductile iron legs, with Ferrus treatment, a protective process for iron that guarantees optimal corrosion resistance.

Materials & Finishes:

Ductile Iron treated with FERRUS: iron protection process that ensures optimal corrosion resistance. The Ferrus treatment consists of three layers applied after cleaning all dirt and impurities using shot blasting, involving an electrolytic bath followed by an epoxy primer and a final coating of polyester powder paint.Forged black colour

Hardwood treated with LIGNUS: Wood from responsible forestry. Density greater than 930kg/m³, at 12% humidity, treated with a triple-layer LIGNUS coating, fungicide, insecticide, and water-repellent that provides protection against moisture penetration. Final finish with a layer of natural pigment in a satin finish, which provides additional protection against UV rays, the main cause of deterioration in this type of material.



Ref.	A	B	H	H1	Wt
UM397E	77.36"	23.62"	32.68"	16.93"	176 Lbs
UM397BE	77.36"	21.46"	18.11"	-	2 Lbs
UM397SE	22.24"	23.62"	32.68"	16.93"	88 Lbs

Leman
UM397BE



Leman
UM397E

V. 2026-04-21 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.

BENITO

info@benito.com
tel. 93 852 1000

Chair **Leman** UM397SE

Downloads: *Maintenance guide* | *Project sheet* | *CAD* | *Mounting instructions* |

V. 2026-04-21 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.